

API-MODIFIED

HIGH-PRESSURE THREAD COMPOUND

DESCRIPTION

JET-LUBE® API-MODIFIED is a high-pressure thread compound that conforms to or exceeds the requirements of API RP 5A3 and former API BUL 5A2. It also contains rust and oxidation inhibitors blended in **JET-LUBE's** unique grease compounded from custom-refined, low-sulfur oil to ensure brushability over a wide temperature range, tenacious adherence to all surfaces, resistance to water washout, and prevention of rust/corrosion.

API-MODIFIED will seal and withstand pressures to 10,000 psi and will not harden or dry.

The lubricating characteristics of **API-MODIFIED** reduces friction in the makeup of casing and tubing, preventing galling and wear. Maximum thread engagement is ensured, providing optimum leak resistance.

Inhibitors in **API-MODIFIED** provide maximum protection against rust and corrosion of threaded surfaces. Its conductivity reduces the possibility of electrolytic corrosion by preventing the formation of galvanic cells in the presence of salt water and other corrosive fluids.

Not recommended for rotary shouldered connections.

- Meets or exceeds API RP 5A3
- Additives for rust & corrosion protection
- Excellent lubrication qualities to prevent galling & wear
- Sticks to wet or oily threads
- Brushable over a wide temperature range
- Leak prevention to 10,000 psi
- Available in Arctic Grade
- California Proposition 65: Carcinogen & reproductive toxin

APPLICATIONS

JET-LUBE API-MODIFIED is specially formulated for use on casing, tubing, line pipe, flow lines, subsurface production tools, tank batteries, and will lubricate, seal and protect threaded connections of oilfield tubular goods on makeup, in service, and in storage.

PRODUCT CHARACTERISTICS

Thickener	Soap
Fluid Type	Petroleum
Color/Appearance	Black/Brown
Dropping Point (ASTM D-2265)	>280°F (138°C)
Specific Gravity	1.97
Density (lbs./gal.)	16.4
Flash Point (ASTM D-92)	>430°F (221°C)
NLGI Grade	1
Penetration @77°F	310 - 340
Friction Factor	1.0
Copper Strip Corrosion (ASTM D-4048)	1A
4-Ball (ASTM D-2596)	1000 Weld Point, kgf >130 Load Wear Index

Shelf Life: Minimum 2 years from manufacture date.

PACKAGING

Code No.	Container Size	Shipping Wt.
22123	10 lb.	11 lbs.
22112	25 lb.	27 lbs.
22114	50 lb.	54 lbs.
22119	25 kg.	27 kg.

LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

CORPORATE LOCATIONS

Houston, Texas—World Headquarters

Maidenhead, England

Edmonton, Canada

JET-LUBE, INC.
4849 HOMESTEAD RD.,
SUITE 232
HOUSTON, TX 77028

WATS: 800-538-5823
PHONE: 713-670-5700
FAX: 713-678-4604
EMAIL: sales@jetlube.com
www.jetlube.com

OILFIELD

OILFIELD

OILFIELD

OILFIELD

OILFIELD

JET-LUBE, INC.

MATERIAL SAFETY DATA SHEET

Product Name: **API-MODIFIED**
Chemical Family: Petroleum based lubricating grease
Use: Tubing, casing and line pipe.

Manufacturer/Supplier: JET-LUBE, INC.
Address: 4849 Homestead Rd., Ste. #200
 Houston, TX, 77028 USA **Phone:** 713-674-7617
Emergency Phone: 713-674-7617 **Fax:** 713-678-4604
Chemtrec 24 hours (USA): 800-424-9300

Hazardous Components	CAS No.	Wt%	OSHA PEL	ACGIH TLV	Other Limits of Exposure
Petroleum oil	64742014/64742525	30-40	Oil mist TWA-5mg/M ³	N/A	STEL: 10mg/M ³
Nonhazardous Blend	94166877/3159624 7620771/7782425	18-23	UN	UN	STEL: UN
Metallic Lead	7439921	29-31	0.05 mg/M ³	0.15/M ³	
Metallic Zinc	7440666	11.6-12.8	15mg/M ³	10mg/M ³	STEL: 10mg/M ³
Metallic Copper	7440508	3-3.6	N/A	1mg/M ³	STEL: 2mg/M ³

Main Hazards—Health Effects

Eyes: May cause irritation. **Inhalation:** Viscous nature may block breathing passages if inhaled. **Ingestion:** May cause diarrhea.
Skin: For hypersensitive persons, may irritate the skin after prolonged periods of contact.

Eyes: Flush with water until all residual material is gone. If irritation persists, seek medical help. **Inhalation:** Clear air passage. If respiratory difficulty continues, seek medical help. **Ingestion:** Wash out mouth immediately. Consult physician. **Skin:** Wash thoroughly with hand cleanser, followed by soap & water. Contaminated clothing should be dry cleaned before reuse.

Extinguishing Media: Foam, dry powder, Halon®, carbon dioxide, sand, earth & water mist.

Unsuitable Extinguishing Media: Water jet. **Protective Equipment for Fire fighting:** Self-contained breathing apparatus.

Personal Precautions: Wear gloves & protective overalls. **Environmental Precautions:** Do not allow it to enter drains.

Spillage: Scrape up bulk, then wipe up remainder with cloth. To prevent walking hazard, pick up remaining residue with diatomaceous earth.

Handling: No special handling precautions necessary.

Storage: Do not store at elevated temperatures.

Respiratory Protection: None needed.

Hand Protection: Protective gloves for hypersensitive persons.

Eye Protection: Glasses, if applied to parts in motion.

Body Protection: Overalls.

Physical State: Semisolid paste **Color:** Black/Brown **Odor:** Petroleum **pH:** Neutral **Boiling Range/Point °F (°C):** >525 (274)

Melting Point °F (°C): >280 (138) **Flash Point (COC) °F (°C):** >430 (221) **Autoignition Temperature °F (°C):** >500 (260)

Explosive Properties: LEL: 0.9% UEL: 7% **Evaporation Rate (Butyl Acetate):** <0.01 **Partition Coefficient (Log Pow):** N/A

Vapor Pressure (kPa): <0.01 **% Volatiles:** Nil **Density (g/cm³):** MOD 1.97 SIL 2.08 **Flammability:** Not flammable at ambient temp.

OSHA Value: N/A **Oxidizing Properties:** None **Water Solubility:** Nil **Vapor Density:** >5

Stability: Chemically stable under normal conditions. No photoreactive agents. **Conditions to Avoid:** Powerful sources of ignition & extreme temps.

Materials to Avoid: Strong inorganic & organic acids, oxidizing agents & metal reactive agents. **Hazardous Decomposition Products:** Burning generates smoke, airborne soot, hydrocarbons and oxides of carbon, sulfur & nitrogen. Residue mainly comprised of soot, metal & mineral oxides.

Acute Toxicity: Not known. **Irritancy—Skin:** Very mild. **Skin Sensitization:** Not known. **Subacute/Sub-chronic Toxicity:** Not known.

Genotoxicity: Yes, lead **Chronic Toxicity:** May result in birth defects, anemia, weight loss & impaired motor functions.

California Prop 65: Lead, Reproductive toxin & carcinogen **Carcinogen:** NTP: No IARC: Probable 2B **OSHA:** No **EC Class (67/548/EEC):** No **LC-50:** UN, presumed toxic **LD-50:** N/A **Allergens:** UN **Tetragens:** Yes, lead. **WHMIS (Canada):** D2A D2B

Possible Effects: May generate oil fractions and lead that could act as a marine pollutants. **Behavior:** Bioaccumulation potential of metallic lead is minimal. **Environmental Fate:** Highly unlikely to cause notable contamination. May be toxic to marine or land organisms. More dense than water with limited solubility or mobility.

Product Disposal: Don't incinerate. Contact waste disposal company or local authority for advice on leaded waste. EPA Waste Code D008

Container Disposal: Pails without liner—see Product Disposal section above. Pails with plastic liner—pail may only be disposed of via standard waste disposal services, recycled or reused. **Liner—**see Product Disposal section above.

D.O.T.: Nonhazardous (insoluble lead)

UN No.: N/A

Air Transport (ICAO & IATA): Nonhazardous

Sea Transport (IMO & IMDG): Nonhazardous (insoluble lead)

Road & Rail Transport (ADR/RID): Nonhazardous


Labeling Information: None **EC Annex 1 Class:** N/A **R Phrases:** R22-harmful if swallowed. R33-danger of cumulative effects.

S Phrases: S41-burning may evolve toxic fumes. **Ozone Depleting Chemicals:** Not applicable. **TSCA:** All components are listed.

EINECS: All components listed. **Canadian DSL:** All components listed. **40 CFR Part 372 (SARA Sec. 313):** Contains lead, zinc & copper

CERCLA: Lead RQ-1 lb. **SARA 311/312 & RCRA Hazard Class:** Hazardous, contains lead. **TSCA 12B Components:** Zinc & Lead

SDS first issued. SDS data revised. **New Jersey Right To Know:** See Section II

Signature: 
Prepared by: Donald A. Oldiges
Date Issued: December 4, 2008

As of issue date, the information contained herein is accurate and reliable to the best of JET-LUBE'S knowledge. JET-LUBE® does not warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising out of the use thereof. It is the user's responsibility to satisfy itself that the information offered for its consideration is suitable for its particular use.

LEGEND

- I. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY
- II. COMPOSITION INFORMATION ON INGREDIENTS
- III. HAZARDS IDENTIFICATION
- IV. FIRST AID MEASURES
- V. FIRE FIGHTING MEASURES
- VI. ACCIDENTAL RELEASE MEASURES
- VII. HANDLING AND STORAGE
- VIII. EXPOSURE CONTROL/PERSONAL PROTECTION
- IX. PHYSICAL AND CHEMICAL PROPERTIES
- X. STABILITY AND REACTIVITY
- XI. TOXICOLOGICAL INFORMATION
- XII. ECOLOGICAL INFORMATION
- XIII. WASTE DISPOSAL
- XIV. TRANSPORT INFORMATION
- XV. REGULATORY INFORMATION
- XVI. OTHER INFORMATION

HMIS SYMBOL

HEALTH	2
FLAMMABILITY	1
REACTIVITY	1
PPI	B

NFPA SYMBOL

