

# JLS<sup>®</sup> (JET-LUBE<sup>®</sup> SPECIAL) TOOL JOINT COMPOUND

## DESCRIPTION

**JLS<sup>®</sup>** Tool Joint Compound is a high quality product containing premium grade copper flake, amorphous graphite, rust and corrosion inhibitors, and other inorganic solids. All are blended in **JET-LUBE's** unique grease compounded from custom refined, low-sulfur oil to ensure brushability over a wide temperature range, tenacious adherence to all surfaces, resistance to water washout, and prevention of rust/corrosion.

**JLS** is a result of laboratory and field development efforts spanning several decades. It is manufactured under the industry's toughest quality control regimen and is especially designed to prevent thread and shoulder wear, and to provide superior performance on the rig floor and downhole in medium duty drilling just as **KOPR-KOTE<sup>®</sup>** and **JET-LUBE 21<sup>®</sup>** perform in more severe conditions. **For inverted muds or high pH muds a special base grease is available.**

- Lead Free
- Zinc Free
- Formulated with a proprietary blend of copper flake, graphite, and other inorganic additives for protection and prevention of excessive circumferential make-up of tool joints in average drilling conditions.
- Unique high temperature grease base with brushability over a wide temperature range.
- Sticks to wet joints.
- Low sulphur content.
- Consistent rig floor make-up.
- Resistance to further make-up downhole in medium drilling.
- **Available in Arctic and Thermal base greases.**

## APPLICATIONS

**JLS** is recommended for use on tool joints in drilling medium depths and formations. It provides consistent control of make-up and break-out in these conditions and protects against galling and seizure. **JLS** prevents excessive stresses which shorten tool joint life, and the metallic solids of **JLS** form a gasket on threads and shoulders that prevent metal-to-metal contact under high torque loads.

## PRODUCT CHARACTERISTICS

Thickener	Aluminum Complex
Fluid Type	Petroleum
Color/Appearance	Black/Brown Paste
Dropping Point (ASTM D-566)	450°F (232°C)
Specific Gravity	1.09
Density (lb/gal)	9.1
Oil Separation (ASTM D-6184)	<3.0
Wtr. % Loss @ 212°F (100°C)	
Flash Point (ASTM D-92)	>430°F (221°C)
NLGI Grade	1½
Penetration @77°F (ASTM D-217)	285 - 315
Copper Strip Corrosion (ASTM D-4048)	1A
Shell 4-Ball (ASTM D-2596)	
Weld Point, kgf	620

## PACKAGING

Code No.	Container Size	Shipping Wt.
11923	1 gal.	10 lb.
11912	2 gal.	20 lb.
11915	5 gal.	47 lb.
11924	15 gal.	140 lb.
11929	50 gal.	489 lb.

## LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery, this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

## CORPORATE LOCATIONS

Houston, Texas—World Headquarters

Maidenhead, England

Edmonton, Canada



JET-LUBE, INC.  
4849 HOMESTEAD RD.,  
SUITE 232  
HOUSTON, TX 77028

US TOLL FREE: 800-538-5823  
PHONE: 713-670-5700  
FAX: 713-678-4604  
sales@jetlube.com  
www.jetlube.com

# JET-LUBE, INC.

## MATERIAL SAFETY DATA SHEET

**Product Name:** JLS®  
**Chemical Family:** Petroleum based lubricating grease  
**Use:** Tool joint compound.

**Manufacturer/Supplier:** JET-LUBE, INC.  
**Address:** 4849 Homestead Rd., Ste. #232  
 Houston, TX, 77028 USA **Phone:** 713-670-5700  
**Emergency Phone:** 713-670-5700 **Fax:** 713-678-4604  
**Chemtrec 24 hours (USA):** 800-424-9300  
**Outside the USA:** 703-527-3887

Hazardous Components	CAS No.	Wt%	OSHA PEL	ACGIH TLV	Other Limits of Exposure
Lubricating Grease	74869219	50-70	N/A	N/A	STEL: 10mg/M <sup>3</sup>
Metallic Copper	7440508	3 - 7	N/A	1mg/M <sup>3</sup>	STEL: 2mg/M <sup>3</sup>
Nonhazardous Blend	7782425/12001262 14807966/1317653	30-50	UN	UN	STEL: UN

### Main Hazards—Health Effects

**Eyes:** May cause irritation. **Inhalation:** Viscous nature may block breathing passages if inhaled. **Ingestion:** May cause diarrhea.  
**Skin:** For hypersensitive persons, may irritate the skin after prolonged periods of contact.

**Eyes:** Flush with water until all residual material is gone. If irritation persists, seek medical help. **Inhalation:** Clear air passage. If respiratory difficulty continues, seek medical help. **Ingestion:** Wash out mouth immediately. Consult physician. **Skin:** Wash thoroughly with hand cleanser, followed by soap & water. Contaminated clothing should be dry cleaned before reuse.

**Extinguishing Media:** Foam, dry powder, Halon®, carbon dioxide, sand, earth & water mist. **Unsuitable Extinguishing Media:** Water jet.  
**Protective Equipment for Fire fighting:** Self-contained breathing apparatus.

**Personal Precautions:** Wear gloves & protective overalls. **Environmental Precautions:** Do not allow it to enter drains. **Spillage:** Scrape up bulk, then wipe up remainder with cloth. To prevent walking hazard, pick up remaining residue with diatomaceous earth.

**Handling:** No special handling precautions necessary. **Storage:** Do not store at elevated temperatures.

**Respiratory Protection:** None needed. **Hand Protection:** Protective gloves for hypersensitive persons.  
**Eye Protection:** Glasses, if applied to parts in motion. **Body Protection:** Overalls.

**Physical State:** Semisolid paste **Color:** Bronze **Odor:** Petroleum **pH:** Neutral **Boiling Range/Point °F (°C):** >525 (274)  
**Melting Point °F (°C):** 450 (232) **Flash Point (COC) °F (°C):** >430 (221) **Autoignition Temperature °F (°C):** >500 (260)  
**Explosive Properties:** LEL: 0.9% UEL: 7% **Evaporation Rate (Butyl Acetate):** <0.01 **Partition Coefficient (Log Pow):** N/A  
**Vapor Pressure (kPa):** <0.01 **Percent Volatiles:** Nil **Density (g/cm<sup>3</sup>):** 1.18 **Flammability:** Not flammable at ambient temperature.  
**OAR Value:** N/A **Oxidizing Properties:** None **Water Solubility:** Nil **Vapor Density:** >5

**Stability:** Chemically stable under normal conditions. No photoreactive agents. **Conditions to Avoid:** Powerful sources of ignition & extreme temps. **Materials to Avoid:** Strong inorganic & organic acids, oxidizing & copper reactive agents. **Hazardous Decomposition Products:** Burning generates smoke, airborne soot, hydrocarbons & oxides of carbon, sulfur & nitrogen. Residue mainly comprised of soot & mineral oxides.

**Acute Toxicity:** Not known. **Irritancy—Skin:** Very mild. **Skin Sensitization:** Not known. **Subacute/Sub-chronic Toxicity:** Not known.  
**Genotoxicity:** None known. **Chronic Toxicity:** None known. **California Prop 65:** N/A **Carcinogen:** NTP: No IARC: No OSHA: No  
**EC Class (67/548/EEC):** No **Allergens:** None known. **LC-50:** >1.98 g/lit(mysidopsis bahia) based on assessment from related products. **LD-50:** N/A

**Possible Effects:** In extreme cases, may generate oil fractions that could act as a marine pollutant. Occurrences of this nature are highly unlikely. **Behavior:** Relatively well behaved. Bioaccumulation potential nil.


**Environmental Fate:** Highly unlikely to cause widespread contamination.

**Product Disposal:** Do not incinerate. Contact waste disposal company or local authority for advice. **Container Disposal:** Pails without liner—see Product Disposal section above. Pails with plastic liner—pail may only be disposed of via standard waste disposal services, recycled or reused. **Liner—**see Product Disposal section above.

Not classified as hazardous for transport. **D.O.T.:** Nonhazardous **UN No.:** Nonhazardous **Air Transport (ICAO & IATA):** Nonhazardous  
**Sea Transport (IMO & IMDG):** Nonhazardous **Road & Rail Transport (ADR/RID):** Nonhazardous

**Labeling Information:** None needed **EC Annex 1 Classification:** Not Applicable. **R Phrases:** R22—harmful if swallowed.  
**S Phrases:** None applicable, as known. **Ozone Depleting Chemicals:** Not applicable. **TSCA:** All components are listed.  
**WHMIS (Canada):** Not controlled. **Canadian DSL:** All components listed. **40 CFR Part 372 (SARA Section 313):** Contains copper  
**CERCLA:** Nonhazardous **RCRA Hazard Class:** Nonhazardous **SARA 311/312:** None **TSCA 12B Components:** None

SDS first issued. SDS data revised. **New Jersey Right To Know:** See Section II

**Signature:**   
**Prepared by:** Donald A. Oldiges  
**Date Issued:** February 12, 2010

As of issue date, the information contained herein is accurate and reliable to the best of JET-LUBE'S knowledge. JET-LUBE® does not warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising out of the use thereof. It is the user's responsibility to satisfy itself that the information offered for its consideration is suitable for its particular use.

### LEGEND

- I. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY
- II. COMPOSITION INFORMATION ON INGREDIENTS
- III. HAZARDS IDENTIFICATION
- IV. FIRST AID MEASURES
- V. FIRE FIGHTING MEASURES
- VI. ACCIDENTAL RELEASE MEASURES
- VII. HANDLING AND STORAGE
- VIII. EXPOSURE CONTROL/PERSONAL PROTECTION
- IX. PHYSICAL AND CHEMICAL PROPERTIES
- X. STABILITY AND REACTIVITY
- XI. TOXICOLOGICAL INFORMATION
- XII. ECOLOGICAL INFORMATION
- XIII. WASTE DISPOSAL
- XIV. TRANSPORT INFORMATION
- XV. REGULATORY INFORMATION
- XVI. OTHER INFORMATION

### HMIS SYMBOL

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PPI	B

### NFPA SYMBOL

