

# JET-LUBE<sup>®</sup> JACKING SYSTEM GREASE<sup>™</sup> ECF<sup>™</sup>

OSPAR Commission - HOCNF

Classification - "Yellow" Rating for Norway

- "E" for the United Kingdom & The Netherlands

## DESCRIPTION

JET-LUBE<sup>®</sup> JACKING SYSTEM GREASE<sup>™</sup> ECF<sup>™</sup> is safe to use in offshore applications since it is metal free and is formulated to conform to the strict North Sea Environmental Guidelines. It utilizes a water-resistant, complex thickener that is enhanced to improve adhesion and provide greater protection against water washoff, wear, and corrosion. JET-LUBE JACKING SYSTEM GREASE ECF contains specially selected solid natural boundary lubricants to provide outstanding galling resistance and lubrication properties. The solid boundary and organic EP additives synergistically combine to produce a superior lubricating film with high-load and low-wear characteristics.

## APPLICATIONS

JET-LUBE JACKING SYSTEM GREASE ECF is designed to lubricate a wide array of heavily loaded gear applications. It can also be used on slides, jacking systems, cantilever type rigs and assemblies, nuts, bolts, and a wide range of other applications - making JET-LUBE JACKING SYSTEM GREASE ECF a nearly universal product.

- Excellent Environmental Properties
- High Load Resistant
- Water Resistant
- Corrosion Resistant
- Nonmetallic
- Safe for Offshore Personnel
- Biodegradable, non-bioaccumulative
- Outstanding Film Strength
- Easy to Apply

This product is formulated to contain no detectable, leachable, volatile organics by EPA Test Method 1311-TCLP number SW846 8260B as determined by independent, 3<sup>rd</sup> party testing. Testing results are available upon request.

## PRODUCT CHARACTERISTICS

Appearance	Beige Tacky Grease
Fluid Type	Synthetic & Vegetable
Thickener	Complex
Specific Gravity	1.26
Density (lbs/gal)	10.55
Cone Penetration @ 77°F (ASTM D-217)	300 - 330
Dropping Point (ASTM D-2265)	>200°F (93°C), typical
4-Ball (ASTM D-2596) (7845) Weld Point, kgf (N)	≥ 800
Gas Evolution typical Oil Separation	None, <1%, typical
Water Leaching 2 hrs. @ 150°F	<5%, typical
Service Rating	-4°F (-20°C) to 300°F (149°C)
EPA 1311-TCLP	Non-detected

## PACKAGING

Code No.	Container Size	Container
25815	44 lb. (20 kg.)	Pail
25816	5 gal.	Pail
25824	15 gal.	Drum
25829	55 gal.	Drum

## LIMITED WARRANTY

Jet-Lube, Inc. makes the Limited Express Warranty that at the date of delivery this product shall be free from defects in Jet-Lube, Inc. materials and workmanship.

This Limited Express Warranty is expressly in lieu of any other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose, and of any other obligation on the part of Jet-Lube, Inc.

The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Jet-Lube, Inc. shall not be liable for incidental or consequential damages.

1011

## CORPORATE LOCATIONS

Houston, Texas—World Headquarters

Maidenhead, England

Edmonton, Canada



JET-LUBE, INC.  
4849 HOMESTEAD RD.,  
SUITE 232  
HOUSTON, TX 77028

WATS: 800-538-5823  
PHONE: 713-670-5700  
FAX: 713-678-4604  
sales@jetlube.com  
www.jetlube.com