



A CSW Industrials Company

# SAFETY DATA SHEET

Issuing Date 16-Jun-2015

Revision Date 07-Mar-2017

Revision Number 1

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

### GHS product identifier

Product Name Jet-Lube Extreme®

### Other means of identification

Product Code(s) 114

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use Lubricants, Greases and Release Products

Uses advised against No information available

### Supplier's details

#### **Manufacturer Address**

Jet-Lube, LLC  
930 Whitmore Dr.  
Rockwall, Texas 75087  
TEL: 972-771-1000  
Toll Free: 1-800-669-6318

### Emergency telephone number

Emergency Telephone Number CHEMTREC: +1-703-527-3887 (INTERNATIONAL)  
1-800-424-9300 (NORTH AMERICA)

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2

### GHS Label elements, including precautionary statements

#### Emergency Overview

Signal Word	Warning
Hazard Statements	
• Causes skin irritation	
• Causes serious eye irritation	



The product contains no substances which at their given concentration are considered to be hazardous to health

**Appearance** Copper, Bronze

**Physical State** Gel.

**Odor** Petroleum like

### Precautionary Statements

#### Prevention

- Wash face, hands and any exposed skin thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.

#### General Advice

- Specific treatment (see supplemental first aid instructions on this label)

#### Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

#### Skin

- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation occurs: Get medical advice/attention.
- Take off contaminated clothing and wash before reuse.

#### Storage

- None

#### Disposal

- None

### Hazard Not Otherwise Classified (HNOC)

Not applicable

### Other information

20% of the mixture consists of ingredient(s) of unknown toxicity.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Graphite	7782-42-5	10-15	*
Copper	7440-50-8	8-13	*
Talc	14807-96-6	1-5	*
Limestone	1317-65-3	1-5	*
Molybdenum (IV) sulfide	1317-33-5	1-5	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

### Description of necessary first-aid measures

#### Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

#### Skin Contact

Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

<b>Inhalation</b>	Move to fresh air. If symptoms persist, call a physician.
<b>Ingestion</b>	Drink plenty of water. Do not induce vomiting without medical advice. Clean mouth with water and afterwards drink plenty of water. If symptoms persist, call a physician.

**Most important symptoms/effects, acute and delayed**

**Most Important Symptoms/Effects** No information available.

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to Physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

Water spray. Carbon dioxide (CO<sub>2</sub>). Foam. Dry powder. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire.

**Specific Hazards Arising from the Chemical**

Burning produces obnoxious and toxic fumes. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Heavy metal compounds

**Explosion Data**

<b>Sensitivity to Mechanical Impact</b>	None.
<b>Sensitivity to Static Discharge</b>	None.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal Precautions** Use personal protective equipment.

**Environmental Precautions**

**Environmental Precautions** See Section 12 for additional Ecological Information. Do not allow material to contaminate ground water system. Prevent product from entering drains.

**Methods and materials for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Cleaning Up** Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Wear personal protective equipment. Ensure adequate ventilation.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep container tightly closed in a dry and well-ventilated place. Keep in a banded area

**Incompatible Products** Strong oxidizing agents. Acetylene. Vinyl compounds.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Graphite 7782-42-5	-	TWA: 15 mg/m <sup>3</sup> total dust synthetic TWA: 5 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 2.5 mg/m <sup>3</sup> respirable dust natural (vacated) TWA: 10 mg/m <sup>3</sup> total dust synthetic (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m <sup>3</sup> TWA: 2.5 mg/m <sup>3</sup> respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume
Talc 14807-96-6	TWA: 2 mg/m <sup>3</sup>	(vacated) TWA: 2 mg/m <sup>3</sup>	IDLH: 1000 mg/m <sup>3</sup> containing no asbestos and <1% quartz TWA: 2 mg/m <sup>3</sup>
Limestone 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> (vacated) TWA: 15 mg/m <sup>3</sup> (vacated) TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> respirable dust TWA: 10 mg/m <sup>3</sup> total dust
Molybdenum (IV) sulfide 1317-33-5	TWA: 10 mg/m <sup>3</sup> Mo inhalable fraction TWA: 3 mg/m <sup>3</sup> Mo respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> Mo	IDLH: 5000 mg/m <sup>3</sup> Mo

*Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:*

#### Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

#### Appropriate engineering controls

##### Engineering Measures

Showers  
Eyewash stations  
Ventilation systems

#### Individual protection measures, such as personal protective equipment

##### Eye/Face Protection

Safety glasses with side-shields. Risk of contact, wear: Goggles.

##### Skin and Body Protection

Impervious clothing. Impervious gloves.

##### Respiratory Protection

None required under normal usage. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

##### Hygiene Measures

When using, do not eat, drink or smoke. Remove and wash contaminated clothing before re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

**Physical State**  
**Odor**

Gel.  
Petroleum like.

**Appearance**  
**Odor Threshold**

Copper, Bronze.  
No information available.

#### Property

pH

#### Values

Neutral

#### Remarks/ - Method

None known

<b>Melting Point/Range</b>	> 315 °C	None known
<b>Boiling Point/Boiling Range</b>	< 316 °C	None known
<b>Flash Point</b>	> 310 °C	None known
<b>Evaporation rate</b>	No data available	None known
<b>Flammability (solid, gas)</b>	No data available	None known
<b>Flammability Limits in Air</b>		
upper flammability limit	7%	
lower flammability limit	0.9%	
<b>Vapor Pressure</b>	<0.01 kPa @ 20°C	None known
<b>Vapor Density</b>	>5 (air = 1)	None known
<b>Specific Gravity</b>	1.17	None known
<b>Water Solubility</b>	Insoluble in water.	None known
<b>Solubility in other solvents</b>	Soluble.	None known
<b>Partition coefficient: n-octanol/water</b>	No data available	None known
<b>Autoignition Temperature</b>	>315 °C / >500 °F	None known
<b>Decomposition Temperature</b>	No data available	None known
<b>Viscosity</b>	No data available	None known
<b>Flammable Properties</b>	Not flammable	
<b>Explosive Properties</b>	No data available	
<b>Oxidizing Properties</b>	No data available	

**Other information**

VOC Content (%)                      None

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

None under normal processing.

**Hazardous Polymerization**

Hazardous polymerization does not occur.

**Conditions to avoid**

Incompatible products.

**Incompatible materials**

Strong oxidizing agents. Acetylene. Vinyl compounds.

**Hazardous decomposition products**

None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure****Product Information**

<b>Inhalation</b>	None known.
<b>Eye Contact</b>	Causes serious eye irritation.

<b>Skin Contact</b>	Causes skin irritation.
<b>Ingestion</b>	Not an expected route of exposure. May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Molybdenum (IV) sulfide	-	-	> 2820 mg/m <sup>3</sup> ( Rat ) 4 h

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Sensitization** No information available.  
**Mutagenic Effects** No information available.  
**Carcinogenicity** Contains no ingredients above reportable quantities listed as a carcinogen.

**Reproductive Toxicity** No information available.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Aspiration Hazard** No information available.

### Numerical measures of toxicity - Product

**Acute Toxicity** 20% of the mixture consists of ingredient(s) of unknown toxicity.

*The following values are calculated based on chapter 3.1 of the GHS document:*

**LD50 Oral** 2606 mg/kg; Acute toxicity estimate

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Aquatic toxicity is unlikely due to low solubility. Based on available data, the classification criteria are not met

LC50/48h/Acartia tonsa = >1000 mg/L EC50/72h/Skeletonema costatum = >1000 mg/L LC50/96h/Scophthalmus maximus = >1000 mg/L

Sea sediment LC50/10d/Corophium sp. = 925-3502 mg/kg

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Copper 7440-50-8	EC50 96 h: 0.031 - 0.054 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: 0.0426 - 0.0535 mg/L static (Pseudokirchneriella subcapitata)	LC50 96 h: 0.0068 - 0.0156 mg/L (Pimephales promelas) LC50 96 h: < 0.3 mg/L static (Pimephales promelas) LC50 96 h: = 0.052 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 0.112 mg/L flow-through (Poecilia reticulata) LC50 96 h: = 0.2 mg/L flow-through (Pimephales promelas) LC50 96 h: = 0.3 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 0.8 mg/L static (Cyprinus carpio) LC50 96 h: = 1.25 mg/L static (Lepomis macrochirus)	-	EC50 48 h: = 0.03 mg/L Static (Daphnia magna)
Talc 14807-96-6		LC50 96 h: > 100 g/L semi-static (Brachydanio rerio)		

**Persistence and Degradability** No information available.

**Bioaccumulation** No information available.

**Other Adverse Effects**

No information available.

### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Methods** Dispose of in accordance with federal, state, and local regulations Where possible recycling is preferred to disposal or incineration.

**Contaminated Packaging** Do not re-use empty containers.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Copper	Toxic

### 14. TRANSPORT INFORMATION

**DOT** Not regulated

**TDG** Not regulated

**MEX** Not regulated

**ICAO** Not regulated

**IATA** Not regulated

**IMDG/IMO** Not regulated

**RID** Not regulated

**ADR** Not regulated

**ADN** Not regulated

### 15. REGULATORY INFORMATION

#### International Inventories

**TSCA** Not determined

**DSL** Not determined

#### Legend

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

#### U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Copper	7440-50-8	8-13	1.0

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper		X	X	

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**U.S. State Regulations****California Proposition 65**

This product does not contain any Proposition 65 chemicals.

**U.S. State Right-to-Know Regulations**

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Graphite	X	X	X		X
Copper	X	X	X	X	X
Talc	X	X	X		X
Limestone	X	X	X		X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION**

<b>NFPA</b>	Health Hazard 2	Flammability 1	Instability 0	Physical and Chemical Hazards -
<b>HMIS</b>	Health Hazard 2	Flammability 1	Physical Hazard 0	Personal Protection X

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 16-Jun-2015  
**Revision Date** 07-Mar-2017  
**Revision Note** Updated company information

**General Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**