



PRODUCT FINDER INDUSTRIAL

AEROSOLS

CATEGORY	PRODUCT	COMMENTS
Anti-Rust	Rust-Guard®	Water-displacing fluid. Dries to a thin waxy film
Anti-Rust, Penetrating Oil	12/34®	Displaces moisture and prevents corrosion. Only available in Canada
Anti-Rust	Z-Plate™	Repairs galvanized surfaces that have been cut
Anti-Rust, Penetrating Oil	769 Lubricant®	Penetrates, displaces water, lubricates, stops rust. Low surface tension for super penetration
Anti-Seize	Kopr-Kote® Anti-Seize	Protects threads from seizing. Bolts, Lug Nuts, etc
Cleaner/Degreaser	Clean-Up™ II	Chlorine-free solvent. Residue-free. Ozone-friendly
Cleaner/Degreaser	Clean-Up™ Plus	Citrus based degreaser. NSF registered C-1
Dry Film Coating	C-Plate™	Use for plating fresh-cut threads. Protects from galling & corrosion
Dry Film Lubricant	Moly-Mist™	Robust anti-wear film that is not easily rubbed off
Electrical Contact Cleaner	PS Terminal™	Rapid cleaning. Residue-free. Compatible with most plastics; see technical data sheet for details
Food Grade Lubricant	Food Grade Silicone	Light-duty fluid lubricant, not a grease. Moisture-resistant
Food Grade Penetrant, Penetrating Oil	Magic Wrench®	Lubricates and prevents rust, Loosens corroded parts. Semi-synthetic formula
Marine Open Gear Grease	Marine-Moly™	For open applications such as gears, slides. Plates on surfaces. Very water resistant. Bentone clay thickener. Contains moly (MoS ₂)
Open Gear Grease	Gear Guard™	Suitable for very high loads. Readily forms an adhesive film. Bentone clay thickener. Contains MoS ₂
Assembly Lubricant/Preservative	Pitless Adapter Lube™	Food grade. Aids assembly, and disassembly when the time comes. Prevents seizing and galling
Wire Rope/Chain Lubricant	WLD™	Highly tenacious, adhesive lubricant containing both molybdenum disulphide (MoS ₂) and graphite. Penetrates the outer strands
Wire Rope/Chain Lubricant	WRL™	Coats the internal strands to prevent friction and wear

ANTI-SEIZES

CATEGORY	PRODUCT	COMMENTS
Aircraft Assembly	Moly Petrolatum	Prevent seizing during assembly or disassembly of aircraft engine spark plugs, threaded fasteners and fittings at temperatures below 800°F (427°C)
Aircraft Spark Plugs, Austenitic Steel	Graphite Petrolatum	Prevents seizing during assembly or disassembly of aircraft engine spark plugs, threaded fasteners and fittings at temperatures below 900°F (482°C)
Aluminum	Zinc Dust Petrolatum	Prevent seizing during assembly or disassembly of threaded or unthreaded components fabricated from aluminum or its alloys
Chemical-Resistant, High-Temperature	Nikal®	Contains pure nickel flake and a nearly inert dispersing solid in a high quality complex base grease that provides unsurpassed protection from rust by water penetration or water wash off
Conductive, Stainless Steel	SS-30™ Extreme	Copper plates mating and sliding surfaces to provide protection against seizure, galling, and heat-freeze
Food Grade	White Knight™	NSF H-1 Registered. Protects metal parts from seizure, galling, rust, corrosion and heat freeze by tenaciously adhering to the metal surface
General Purpose, High Temperature, Copper	Kopr-Kote® Anti-Seize	NSF H-2 Registered. Suitable for high load. Not for use on aluminum. 1800°F. (980°C). Provides a shield against metal-to-metal contact, preventing seizure and corrosion. provides low friction and cushions impact and shock loads
High-Temperature	Nikal® Nuclear	Contains pure nickel flake. Certified for use at nuclear power plants. Superior protection against rust and corrosion
Marine, Non-Metallic	Marine Grade Anti-Seize	Resists water and prevents rust in salt water environments. Suitable for use on stainless steel
Non-Metallic, General Purpose	550®	Protection against seizure and heat-freeze, eases assembling and dismantling
Non-Metallic. Low "E", General Purpose	550® Extreme®	Water-resistant. For use on steel, aluminum and cast iron. Can be used up to 2400°F (1315°C). 550® Extreme® All Weather Available
Water-Resistant, High Temperature	Silver Plus Regular	Use on rough cut threads, black iron, aluminum. Provide a protective film against galling and seizure over a wide range of applications

CHAIN LUBRICANTS

CATEGORY	PRODUCT	COMMENTS
High Temperature, Semi-Fluid	Oven Chain Lubricant	NSF H-1 Registered. White. Soft grease with non-melt thickener and fully synthetic oil
Penetrant Oil, Mineral Oil	WRL™	Medium viscosity (Approx. ISO 22). Available in aerosol
Penetrant Oil, Semi-Synthetic	Magic Wrench®	NSF H-1 Registered. Semi-synthetic. Medium viscosity. Available in aerosol
Lubricant and Penetrant	769 Lubricant®	NSF H-2 Registered. High penetration and rust protection Low viscosity (Approx. ISO 10). Available in aerosol
Semi-Fluid	WLD™	Black, sticky, semi-fluid. Protects ropes, sheaves and drum face (lagging) under extreme pressure. Available in aerosol
Lubricant and Penetrant	12/34®	Loosens rusted metal parts by means of super "creepability". Only available in aerosol. Only available in Canada

CLEANERS & DEGREASERS

CATEGORY	PRODUCT	COMMENTS
Cleaner /Degreaser, Water-based	Easy-Clean® Liquid	High pH (14). Can be diluted with water. Ideal for pressure washing
Degreaser, Solvent Type, Non-Chlorinated	Clean-Up™ II	Dissolves and rinses away dirt, grease, grime, oil, tar and wax. Residue-free. Ozone-friendly. Low VOC's. Only available in aerosol
Degreaser, Solvent type, Citrus Source	Clean-Up™ Plus	Removes grease, dirt, tar. Environmentally preferable. NSF registered C-1. Available in aerosol.
Electrical Contact Cleaner	PS Terminal™	Rapid cleaning. Residue-free. Compatible with most plastics; see TDS for details. Available in aerosol.

DRY FILM LUBRICANT

CATEGORY	PRODUCT	COMMENTS
Moly (MoS ₂)	Moly-Mist™	Robust lubricating film is not easily scratched or washed off

FOOD MACHINERY

CATEGORY	PRODUCT	NSF	COMMENTS
Anti-Seize	White Knight™	H-1	CFIA approved
Cleaner/Degreaser	Clean-Up Plus™	C-1	Citrus based. Available in aerosol
Electrical Contact Cleaner	PS Terminal™	K-2	Non-flammable. Compatible with most plastics; see tech data sheet for details. Available in aerosol
Gear Oil, Mineral	Gear Oil FG	H-1	Kosher and Halal approved. Available in SAE 80W-90 & 85W-140 and ISO 680 & 1000
Grease, Semi-synthetic oil	CC-Lube™	H-1	NLGI grades: 1 &1.5 & 3 Colorless. Aluminum complex thickener
Grease, Mineral oil	FMG™	H-1	NLGI 0, 1, and 2. White. Contains bacteriostatic agent. Aluminum Complex. Kosher and Halal approved
Grease	White Lithium Grease	H-2	NLGI grade 2. Contains PTFE
Grease, Mineral	CSC Grease FG	H-1	NLGI 2. Off-white, Calcium Sulfonate Complex Base. Kosher and Halal approved
Hydraulic Oil, Mineral	Hydraulic Oil FG	H-1	Kosher and Halal approved. Available in ISO grades 32, 46, 68 and 100
Oven Chains	Oven Chain Lube	H-1	White semi-fluid grease
Penetrating Oil	Magic Wrench™	H-1	Lubricates and prevents rust. Excellent chain lubricant. CFIA approved. Available in aerosol
Silicone Emulsion (Fluid)	EMS™	--	Clean, clear lubricant. Freeze/Thaw stable
Thread Sealant	V2®	P-1	Use on plumbing connections for potable water

GREASES, BEARING

CATEGORY	PRODUCT	COMMENTS	THICKENER
Biodegradable	Alco-EP™ ECF™	Excellent rust protection. Pale red color. NLGI grade 2	Calcium Sulfonate Complex
Electric Motor Bearings	CB-2™	Suitable for high speeds to 300,000 DN. NLGI 2	Lithium (no moly)
Food Grade (H-1)	CC-Lube	Colorless. Semi-synthetic. Grades available: 1.5	Aluminum complex
Food Grade (H-1)	CSC Grease FG 2	Colorless. Semi-synthetic. Grades available: 1, 1.5, 3	Calcium Sulfonate Complex

Food Grade (H-1)	FMG™	White. Contains bacteriostatic agent. NLGI grade 2	Aluminum complex
Food Grade (H-2)	White Lithium Grease	Contains PTFE. NLGI grade 2	Lithium with PTFE (Teflon®)
High Load	Alco EP™	Multi-purpose. Has MoS ₂ and high EP properties. NLGI grade 2	Aluminum complex with moly
High Load	EP Bearing Grease™	Multi-purpose. No solid lubricants. Purple. NLGI grade 2	Lithium
High Load	Jet-Plex EP™	For slow-moving, heavily-loaded applications. Red. Grades 2	Lithium complex
High Load	Jet-Red™	Suitable for heavily loaded applications. Red. NLGI 2.	Lithium Complex
High Temperature	AP-1™	Non-melt. Clear amber color. NLGI 2	Bentone clay
High Temperature	AP-1W™	Non-melt. White. NLGI 2	Bentone clay
High Temperature	AP-5™	Non-melt. With moly. Grade 2	Bentone clay with moly
High Temperature	Kiln Grease HT™	It's not just for kilns. Green. NLGI grade 2	Aluminum complex
High Temperature	Temp-Guard	Non-melt. Black. Contains moly. Grade 1.5	Bentone clay thickener with moly
Low Temperature	Arctic™	Usable to -65°F (-54°C)	Calcium soap
Marine	Alco-EP™ ECF™	EP biodegradable grease. Excellent rust protection. NLGI 2	Calcium sulfonate complex
Marine	Marine MP™	Tacky and water-resistant EP Grease. Purple. NLGI grade 2	Lithium
Multi-purpose	Jet-Red™	Allows users to streamline applications. Red. NLGI 2.	Lithium Complex
Multi-purpose with moly	#202 Moly-Lith™	Extreme pressure grease with MoS ₂ . NLGI 2. Black	Lithium with moly
Multi-purpose without moly	EP Bearing Grease™	Extreme pressure grease without MoS ₂ . NLGI grade 2. Purple	Lithium (no moly)
Water resistant	Alco EP 73 Plus	Sticky red grease. NLGI grade 2	Aluminum complex
White lithium grease	Jet-Lube White Lithium Grease	NLGI grade 2. H-2 registered for food plants. Contains PTFE	Lithium with PTFE (Teflon®)

GREASES, SILICONE

CATEGORY	PRODUCT	COMMENTS
Food Grade	MP Silicone™ (Grade 1.5)	These two silicone greases are identical except for NLGI grades. Use to lubricate O-rings, plastic components and lightly loaded applications, especially in refrigeration systems. All are registered H-1 with NSF
	Silicone Compound DM™ (NLGI Grades 2 & 3)	Range: -70°F to 400°F (-55°C to 200°C)

MARINE APPLICATIONS

CATEGORY	PRODUCT	COMMENTS
Anti-Rust	Rust-Guard	Low viscosity fluid penetrates, displaces water, dries to a thin waxy film. Available in aerosol
Anti-Seize	Marine Grade Anti-Seize	Resists water and prevents rust in salt water environments. Can be used on stainless steel
Cleaner, Degreaser	Easy-Clean® Liquid	High pH (14). Can be diluted with water. Ideal for pressure washing
Degreaser, Citrus	Clean-Up™ Plus	Dissolves grease and tar. Available in aerosol
Grease	Marine MP™	NLGI grade 2. Tacky and water-resistant EP Grease. Purple
Open Applications (Open gears etc.)	Marine-Moly™	Available in 1-lb brush-top cans. Available in aerosol
Penetrating Oil	769 Lubricant®	Penetrates, displaces water, lubricates, stops rust. Available in aerosol
Wire Ropes	Marine Wire Rope and Hawser Grease	NLGI 2 grade grease. Tacky and water-resistant. Protects ropes and sheaves

OPEN GEARS (& OTHER OPEN APPLICATIONS)

CATEGORY	PRODUCT	COMMENTS	THICKENER TYPE	FOUR BALL WELD POINT
Eco-Responsible	Jacking System Grease ECF™	NLGI grade 1. Used on open components of off-shore oil rigs	Calcium sulfonate complex	>800 kg
High Extreme Pressure Protection	OG-H™	NLGI grade between 1 & 2. Black, sticky grease with MoS ₂	Non-melting Bentone clay	620 kg
Marine Open Applications	Marine-Moly™	NLGI grade 2. Available in 1-lb brush-top cans. Available in aerosol	Non-melting Bentone clay	315 kg
Moly Paste	MP-50™	Contains 50% MoS ₂	Non-melting Bentone clay	250 kg
Semi-Fluid Grease	Gear Guard™	NLGI grade 000. Available in aerosol	Non-melting Bentone clay	620 kg

PENETRATING OILS

CATEGORY	PRODUCT	COMMENTS
Low Viscosity	769 Lubricant® (ISO viscosity grade 10)	NSF H-2 Registered. Mineral oil. Loosens rusted nuts and bolts. Stops rust. Available in aerosol
Medium Viscosity, Food Grade	Magic Wrench® (ISO grade 32)	NSF H-1 Registered. Food grade. Synthetic ester oil assures excellent penetration despite higher viscosity. Available in aerosol

RUST INHIBITORS

CATEGORY	PRODUCT	COMMENTS
Fluid Type	12/34®	Displaces moisture and prevents corrosion. Only available in Canada. Only available in aerosol
Fluid Type	769 Lubricant®	Light penetrating oil, displaces water, lubricates. Available in aerosol
Fluid Type	Rust-Guard®	Six months outdoor, one year indoor. Available in aerosol
Grease Type	Korr-Guard™	At least one year of protection outside

THREAD SEALANTS

CATEGORY	PRODUCT	COMMENTS
Metal-Free, Heavy Duty	TF-25™	PTFE. Water-resistant, non-hardening, and has a wide variety of applications
Multi-Purpose	Petro-Tape™	Industrial grade PTFE seal tape. ≥3-mil thick. Contains a light green pigment for easy identification. Heavy duty
Multi-Purpose specially for Stainless Steel	Petro-Tape™ Nickel	Industrial grade PTFE seal tape. ≥4-mil thick. Contains a gray pigment for easy identification. Heavy duty
Multi-Purpose, Plastic (CPVC & ABS), Pressurized Systems, Sprinkler Systems	TFW™	Excellent sealant for pressurized systems. Air, water, natural gas, Excellent thread sealant
Multi-Purpose, Water, incl. potable	V2®	PTFE. NSF P-1

THREAD LOCKER

CATEGORY	PRODUCT	COMMENTS
“Permanent”, Very High Strength	Jet-Lok® III	Two-part epoxy. Replaces welding, but connection can be broken by heating to 550°F (288°C). One hour cure time

WIRE ROPE LUBRICANTS

CATEGORY	PRODUCT	COMMENTS
Grease Type	Marine Wire Rope and Hawser	NLGI 2 grade grease. Lithium. Tacky and water-resistant. Protects ropes and sheaves
Penetrating	WRL™	Medium viscosity (ISO 22). Coats internal strands. Prevents friction and wear. Available in aerosol
Penetrating	Magic Wrench®	Semi-synthetic. Medium viscosity (ISO 32). Available in aerosol
Super Penetrant	769 Lubricant®	High penetration and loosening effect. Rust protection. Low viscosity (approx. ISO 10). Available in aerosol
Semi-Fluid	WLD™	Black, sticky. Coats and protects under extreme pressure. (620 kg weld point on 4-Ball machine)



JET-LUBE®

For more product information,
visit jetlube.com or scan the QR code