SEAL WRAP[™]

DEACON®

WATER ACTIVATED FIBERGLASS WRAP SYSTEM



DEACON[®] SEAL WRAP[™] solutions are engineered to tackle pipe-related challenges. From fast and slow cure reinforcements to high-temperature resilience, our wateractivated fiberglass wrap system ensures your pipes, tanks, and pressure vessels are fortified, sealed, and maintained.

CHEMICAL RESISTANCE

| Alcohols | Excellent | |
|----------------------------|-----------|--|
| Alkalis | Excellent | |
| Dilute Inorganic Acids ——— | Very Good | |
| Hydrocarbons | Excellent | |
| Organic Acids | Good | |
| Salts | Excellent | |
| Solvents | Good | |

APPLICATIONS

BENEFITS

- Leak Repair
- Structural Reinforcement •
- Impact Protection
- Abrasion Resistance
- Quick and Easy Installation
 - Cures in Minutes
- Restores Piping Beyond **Original Capacities**
 - Safe, Nontoxic, and Odorless

Available in three versions to fit your application needs.

| | Deacon Seal Wrap | Deacon Seal Wrap FC | Deacon Seal Wrap SC |
|-----------------------|--|---------------------|---------------------|
| Characteristic | High-Temp & Extreme Chemical Resistance | Fast-Curing | Slow-Curing |
| Cure Time 77°F (25°C) | 15 minutes | 5 minutes | 30 minutes |
| Max Temp Rating | 425°F (218°C) | 250°F (121°C) | 250°F (121°C) |
| Color | White | Black | White |
| Available Sizes | 2" x 30' 4" x 15' 4" x 30' 6" x 25' | 4" x 15' | 4" x 30' |





Learn more jetlube.com/product/ seal-wrap-wateractivated-wrap

